Implementing Open vSwitch datapath using TC

Jiří Pírko jiri@resnulli.us Red Hat

What? Why?

- Goal:
 - Provide an alternative approach to the current OVS kernel datapath
 - Eventually remove OVS kernel datapath completely
- Motivation:
 - Increasing amount of features is implemented in multiple kernel parts
 - Prevent code duplication
 - Easier maintainability
 - Lower bug amount -> happier user
 - Hardware offload do it in one place instead of two
 - It should have been done this way from the very beginning

OVS kernel datapath overview

- Match-action forwarding datapath
- Flow
 - Inherited from OpenFlow standard
 - Consists of:
 - Flow key represents a set of fields in a packet to match
 - Flow mask bitmask for flow key
 - Actions set of various actions to be executed in case packet matches the key with mask
- Vports
 - Could be backed by a real netdevice (eth0)
 - Multiple vports are put into group called "bridge"
 - A bridge is represented by an "internal vport" backed by a netdevice
 - Tunnels (VXLAN, Geneve, GRE)
 - Not represented by netdevices

Classifier-Action subsystem of TC

- Present in kernel for ages (older than git kernel tree)
- Details explained in Jamal's talk/tutorial
- Consists of:
 - Classifiers
 - Do matching on packets
 - cls_32, cls_bpf, ...
 - Actions
 - Executed upon match
 - Chains
 - act_skbedit, act_nat, act_mirred, act_vlan, ...

Using TC Classifier-Action to implement OVS kernel DP

- TC CA and OVS both do match-action processing
- Why not to replace OVS by TC CA?
 - Many of needed TC CA features are already in place
 - Some of them are not
 - So implement them
- Classifiers attached to ingress qdisc

tc qdisc add dev eth0 ingress tc filter add dev eth0 parent ffff: protocol all u32 match u32 0 0 \ action mirred egress redirect dev eth1 tc qdisc add dev eth1 ingress tc filter add dev eth1 parent ffff: protocol all u32 match u32 0 0 \ action mirred egress redirect dev eth0

Ok, so what do we need?

The classifier

- cls_u32 could be able to cover
 - Some wrapper would be needed
 - Generic probably has performance impacts
- cls_openflow a new one
 - Implements matches on OpenFlow essential items
 - Planned to implement all items OVS uses

tc qdisc add dev eth0 ingress tc filter add dev eth0 parent ffff: protocol all openflow \ src_ip 192.168.0.1 dst_ip 192.168.10.0/24 \ action mirred egress redirect dev eth1

Actions

- Output action
 - act_mirred
- Upstream output action
 - In case of a flow-miss
 - Forward to a tap device
- VLAN header pop and push actions
 - act_vlan
- MPLS
 - Similar to VLAN to some extend
 - Not implemented in TC CA yet

tc qdisc add dev eth0 ingress tc filter add dev eth0 parent ffff: protocol all openflow \ src_ip 192.168.0.1 dst_ip 192.168.10.0/24 \ action mirred egress redirect dev eth1

Tunneling

- VXLAN, Geneve, GRE, ...
- In OVS tunnels are virtual ports without any netdevice
 - Open tunnel socket, register a rx function, on tx call tx function
- For TC, create a netdevice for tunnel and use it as any other netdevice
 - Not all tunnels available (Geneve)
 - Scalability issues (netdevice for thousands of tunnels)
- Tunnel action?
 - Action created socket and uses tx function for tx
 - Nowhere to hook on receive path
- Use "named" sockets
 - Create tunnel socket from userspace
 - Name it
 - Use in TC rules instead of netdevice

Named tunnel socket example

Other approaches

- nftables?
- eBPF?

The end

• Questions?